

Product Specifications	36XT
Working Height	43' 6"
Platform Height	37' 6"
Platform Capacity (lbs)	500
Maximum Outreach	32'
Turntable Rotation (°)	700° Non-Continuous
Platform Rotation (°)*	120° Manual
Platform Size	5' x 2' 6"
Width	5' 6"
Height Stowed	6' 6.5"
Length Stowed	20' 8.75"
Ground Clearance	6"
Wheelbase	8' 8.5"
Outrigger Type	Hydraulic
Leveling System	Automatic
Leveling Capability	12.5°
Gradeability	45%
Outrigger Footprint (LxW)	12' 2" x 11' 3.5"
Weight (lbs)	5100
Tire Size	26 x 12
Engine (horsepower)	21
Voltage	24
Battery (Amp/h)	245



*Optional

Lightweight Self-Propelled Booms
36XT





Lightweight Self-Propelled Booms

36XT

Features/Benefits

Automatic leveling provides set-up in less than 30 seconds

Hydraulic outriggers with interlocks and tilt alarm/sensor

Intuitive control system

Air and water lines to platform standard

4500 watt generator and 110V GFI protected electrical outlets to platform and base

Self-leveling platform

Hour meter and battery condition indicator



Product Specifications	45XA	NiftyLift SP45
Working Height	51'	51' 8"
Platform Height	45'	45' 1"
Platform Capacity (lbs)	500	500
Maximum Outreach	27'	31' 6"
Jib Range of Motion	-80°/+70°	N/A
Turntable Rotation (°)	700° Non-Continuous	360° Non-Continuous
Platform Rotation (°)*	120° Manual	180° Manual
Platform Size	5' x 2' 6"	5' 11" x 2' 4"
Width	5' 6"	6' 7"
Height Stowed	6' 6.5"	7' 2"
Length Stowed	18' 2"	16' 5"
Ground Clearance	6"	N/A
Wheelbase	8' 8.5"	N/A
Outrigger Type	Hydraulic	N/A
Leveling System	Automatic	N/A
Leveling Capability	12.5°	N/A
Gradeability	45%	45%
Outrigger Footprint (LxW)	12' 4" x 11' 4"	N/A
Weight (lbs)	4900	14110
Tire Size	26 x 12	N/A
Engine (horsepower)	21	32
Voltage	24	N/A
Battery (Amp/h)	245	N/A



*Optional

Lightweight Self-Propelled Booms
45XA





Lightweight Self-Propelled Booms

45XA

Features/Benefits

Automatic leveling provides set-up in less than 30 seconds

Hydraulic outriggers with interlocks and tilt alarm/sensor

Intuitive control system

Air and water lines to platform standard

4500 watt generator and 110V GFI protected electrical outlets to platform and base

Self-leveling platform

Hour meter and battery condition indicator



Product Specifications	55XA	NiftyLift
Working Height	61' 3"	59' 1"
Platform Height	55' 3"	52' 6"
Platform Capacity (lbs)	500	500
Maximum Outreach	33' 5"	32' 4"
Jib Range of Motion	-80°/+70°	130°
Turntable Rotation (°)	700° Non-Continuous	360° Non-Continuous
Platform Rotation (°)*	120° Manual	180° Manual
Platform Size	5' x 2' 6"	4' 11" x 3' 1"
Width	5' 8"	7' 5"
Height Stowed	6' 6"	7' 10"
Length Stowed	21' 2"	23' 4"
Ground Clearance	10"	N/A
Wheelbase	12' 1"	N/A
Outrigger Type	Hydraulic	N/A
Leveling System	Automatic	N/A
Leveling Capability	12.5°	N/A
Gradeability	45%	50%
Outrigger Footprint (LxW)	12' 4" x 11' 4"	N/A
Weight (lbs)	4900	13900
Tire Size	26 x 12	N/A
Engine (horsepower)	21	32
Voltage	24	N/A
Battery (Amp/h)	245	N/A

Lightweight Self-Propelled Booms
55XA



*Optional



Lightweight Self-Propelled Booms

55XA

Features/Benefits

Automatic leveling provides set-up in less than 30 seconds

Hydraulic outriggers with interlocks and tilt alarm/sensor

Intuitive control system

Air and water lines to platform standard

4500 watt generator and 110V GFI protected electrical outlets to platform and base

Self-leveling platform

Hour meter and battery condition indicator

