

Effective: September 13, 2004

### Now 3 Models to Choose From

- Three-leg design allows the lift to be positioned closer to walls
- Holds 4' x 12' sheets of drywall
- Winch design uses a steering wheel for easy adjustment
- Large 4" casters with side lock
- Knocks down for easy transporting - easy to assemble
- Drywall lift head features:
  - Rigid design for secure placement of drywall board
  - Quick adjusting arms accommodate 8' or 12' drywall board
  - Tilting, 360° rotating head to service cathedral ceilings and give greater flexibility

### DL 100

- 5' to 10' lifting height
- Heavy duty lifting cable
- Quick locks for the legs
- Base is designed for easy set up



### DL 125

- 5' to 12' lifting height
- 60" tall (without head)
- 38" loading height
- Heavy duty dual lifting cables for additional cable life
- 30" outriggers - collapse to 8" radius for storage
- Automatic brake
- Casters stay in contact with ground, even when outriggers are collapsed, so lift is easy to maneuver at all times.



### DL 150

- 6-1/2' to 15' lifting height
- 68" tall (without head)
- 47-1/2" loading height
- Heavy duty dual lifting cables for additional cable life
- 30" outriggers - collapse to 8" radius for storage
- Automatic brake
- Casters stay in contact with ground, even when outriggers are collapsed, so lift is easy to maneuver at all times.



The DL 100 comes with a replacement cable. Models DL 125 and DL 150 are accompanied with two replacement cables. Cables should be replaced annually and more frequently if fraying occurs.

PART NO.	DESCRIPTION	CAP#	WT#
0063-0547	Model DL 100, Steel, 5' to 10' Lift Adjustment	200	104
0063-0580	Model DL 125, Steel, 5' to 12' Lift Adjustment	200	125
0063-0595	Model DL 150, Steel, 6-1/2' to 15' Lift Adjustment	160	141

125 Taylor Parkway • Archbold, Ohio 43502-9309  
(419) 445-8915, (800) 537-0540 • Fax (419) 445-0367 • [www.biljax.com](http://www.biljax.com)